



Image depicts 12 x 12 inch section

Colorways



© 2021 Wolf-Gordon Inc. All Rights Reserved
1-800-347-0550

Watson WTS 6473 Pebble

Physical Properties

Content: 88% Polyester, 12% Thermoplastic Elastomer

Finish: Tekloom® TPE Graffiti-proof treatment

Width: 54"

Weight: 20.00 oz per linear yard

Performance

Wet and Dry Crocking: Passes AATCC 8--Wet: Class 5;

Breaking Strength: Passes ASTM D5034--Warp: 321 lbs; — Weft: 270 lbs

Seam Slippage: Passes ASTM D4034--Warp: 74.5 lbs; — Weft: 60.5 lbs

Marine Applications: IMO FTP Code 2010 - Pass

Marine Applications: IMO FTP Code 2010 - Pass

Abrasion: 1,000,000 double rubs, Wyzenbeek

Colorfastness to Light: Passes AATCC 16--Grade 5 @ 40 hours

Flame Resistance: Passes Cal TB 117-2013, without flame retardant|
Passes NFPA 260/UFAC

Cleaning Code: W-S = Clean with either a water- or solvent-based agent; a diluted bleach solution can be used

Sustainability

Free of Conflict minerals, Flame-retardant chemicals, PFC/PFOA, phthalates(BBP, DBP, DEHP, DIDP, DINP, DnHP, DnOP), PVC
Printed with solvent-free inks

Pricing

\$58.75 per linear yard